


Physics-Based Simulations of Fluid/Structure/Dynamics Interactions in Scenarios Associated with Blast



Yang Yang, William W. Liou
Western Michigan University
Kalamazoo, Michigan

James Sheng, David Gorsich, Sudhakar Arepally
TARDEC, U.S. Army RDECOM
Warren, Michigan




This material is based upon work supported by the U.S. Army TACOM Life Cycle Command under Contract No. W56HZV-08-C-0236, through a subcontract with Mississippi State University, and was performed for the Simulation Based Reliability and Safety (SimBRS) research program. Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the U.S. Army TACOM Life Cycle Command.



Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 06 AUG 2010		2. REPORT TYPE N/A		3. DATES COVERED	
4. TITLE AND SUBTITLE Physics-Based Simulations of Fluid/Structure/Dynamics Interactions in Scenarios Associated with Blast				5a. CONTRACT NUMBER W56HZV-08-C-0236	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) ; ; ; Yang YangLiou William W.Sheng JamesGorsich DavidSudhakar Arepally US Army RDECOM-TARDEC 6501 E 11 Mile Rd Warren MI 48397-5000, USA				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Western Michigan University Kalamazoo, MI USA				8. PERFORMING ORGANIZATION REPORT NUMBER 21083RC	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) TACOM/TARDEC				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 15	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Objectives

- ❑ **Develop vehicle occupant blast load simulation**
 - **Fast and accurate - Physics and HPC**
 - **Cost efficient – Open source code**
 - **Flexible and User-friendly**



Outlines

- ☐ Background
- ☐ Technical Approach
- ☐ Results and Discussion
- ☐ Summary

IED and TBI

Improvised Explosive Device (IED)

- Over 60% of the blast injury in OEF and OIF in 2009
- Penetration and direct injuries
- Remains weapon of choice and major threats
- Survival rate increased with armor (head, body)

Blast Traumatic Brain Injury (TBI)

- “Signature” injury in OEF and OIF
- Primary blast injury caused by blast induced pressure change
- Battle field and in-theater innovations in treatment lowered killed:wounded ratio
- Simulation to further enhance vehicle occupant survivability

Fundamental Physics and Simulation

Gas Dynamics - CFD

- Spatial (three-dimensional) and temporal (time accurate)
- High pressure ratio wave of small time scale
- Pressure wave numerical resolution in 3D
- Moving/deforming immersed boundary
- Computationally intensive

Computational Structural Dynamics - CSD

- Spatial (three dimensional) and temporal (time-accurate)
- Materials dynamic behavior
- Large deformation or fragmentation
- Computationally intensive

Motion Dynamics – 6DOF


- Kinematics and dynamics of body motion
 - Six degree of freedom (6DOF) motion equations
- Computationally intensive



Simulation Platform (1)

Fluid Dynamics and Structural Dynamics Virtual Test Facility (VTF) from Cal Tech

- Developed at Cal Tech's Center for Simulation of Dynamic Response of Materials.
- 3D dynamic response of materials subjected to strong shocks and detonation waves propagate in fluids
- Explicitly coupled Eulerian-Lagrangian simulations
- Adaptive mesh refinement for Cartesian finite volume fluid solver
- High order sub-division FE thin-shell structure solves
- Fracture and fragmentation
- Highly parallelized CFD and CSD solvers
- Open-source



Simulation Platform (2)

Rigid Body Motion Dynamics


WMU Enhanced Solver

- Geometry flexibility
- Directly coupled to VTF with multiple bodies
- Open-source


Coupled Fluid/Structure/Dynamics Solver

- Vehicle Occupants Blast Load
- High Performance
- Low Cost

Massively Parallel Computing




Adaptive Mesh Refinement




Free Air Blast Wave Propagation

- $P_{\text{TNT}} = 2.89 \text{ GPa}$
- Base Mesh: 200x150x50
- Two Pressure Loads




Metal Plate in TNT Blast (1)




- 150 g C4
- Two standoff distances
- AL6XN SS plate thickness 1.9 mm
- 8 Compute Node


Pressure Contours at T_0




$T_0 +$




$T_0 ++$




Metal Plate in TNT Blast (2)




SS Plate Centerpoint
Deformation History




SS Plate Deformation
Contours



Blast Over Hemisphere Dome (1)




Adaptive CFD Mesh




pressure sensor

Rooftop Pressure Load




Blast Wave Pressure at Sensor




Unclas: Dist A. Approved for public release


Blast Over Hemisphere Dome (2)






- 3 Level of adaptive mesh refinement
- Total # of cell adapt to accuracy need
- Efficient parallel-computing simulation



Blast off Boxes (1)






- Two boxes with one centrally located inside the second
- The outer box deforms elastically; the inner box rigid and fixed in space





Pressure Contours & Box Deformation

Blast off Boxes (2)

- Blast initiated under a single rigid box
- Unconstrained body motion by 6-DOF



Body 6-DOF Motion & Pressure Contours



Concluding Remarks

- ❑ Developed physics-based computer simulations of the effects of fluid-structure interactions due to blast
 - ❑ Open-source software offers accurate and fast simulations
 - ❑ CFD in multiply connected domain
 - ❑ Generic geometries
- ❑ Developed fluid-structure-dynamics interactions mutiphysics solver
 - ❑ Vehicle occupant motion and deformation due to direct/indirect exposure to blast wave
- ❑ In the future,
 - ❑ Apply to realistic dummy model
 - ❑ Develop and couple multi-body dynamics capability for human-like dummy model
 - ❑ Deliver software for time-accurate vehicle occupant blast wave load simulations to TARDEC

